

Product Highlights

Wireless AC and Gigabit Ethernet

Stream HD video or make Internet voice calls across your home, using the fastest wired and wireless connectivity options available today

Dual-band Wi-Fi for Seamless Performance

Access your network via two concurrent wireless bands for seamless performance no matter what you are doing

Simple, Secure Setup

Set up the DIR-842 in no time with the web-based setup wizard, and create a secure wireless connection easily using Wi-Fi Protected Setup (WPS)



DIR-842

AC1200 MU-MIMO Wi-Fi Gigabit Router

Features

High-Speed Connectivity

- 802.11ac wireless specification delivers blazing fast wireless connectivity with increased range and reliability
- 10/100/1000 Gigabit Ethernet WAN port for speedy Internet access
- Four 10/100/1000 Gigabit Ethernet LAN ports give you high-speed wired connectivity

Flexible Bandwidth

- Concurrent dual-band wireless for connections up to 1200 Mbps¹
- Supports MU-MIMO (AC Wave II)
- Supports D-Link Intelligent QoS Technology to prioritize important traffic and deliver uninterrupted bandwidth

Setup and Management

- Web browser-based setup and configuration
- Setup wizard to guide you through the configuration process
- Firewall and access control options to prevent attacks and restrict access to your network

The DIR-842 AC1200 MU-MIMO Wi-Fi Gigabit Router is a powerful wireless networking solution designed for Small Office/Home Office (SOHO) environments. By combining high-speed 802.11ac Wi-Fi specification with dual-band technology and Gigabit Ethernet ports, the DIR-842 provides a seamless networking experience with a high degree of convenience and flexibility for SOHOs. The DIR-842's SOHO-class advanced security features keep data safe from unwanted network intruders. This together with the increased range and reliability of Wireless AC technology, helps provide a safe and secure network for devices further into your home or office.

High-Speed Wired and Wireless Connectivity

The DIR-842 AC1200 MU-MIMO Wi-Fi Gigabit Router upgrades your network to the latest high-speed wireless technology to bring you lightning-fast Wi-Fi speeds of up to 1200 Mbps¹ so you can meet the ever-greater demand from multimedia applications. Enjoy streaming media, Internet phone calls, online gaming, and content-rich web surfing throughout your home or office. In addition, 10/100/1000 Gigabit Ethernet ports give you solid, dependable wired performance for devices such as NAS, media centers, and gaming consoles. The built-in D-Link Intelligent QoS technology allows you to prioritize important traffic to ensure that your favorite applications are receiving optimal bandwidth.

Dual Band Wireless for Seamless Performance

The DIR-842 AC1200 MU-MIMO Wi-Fi Gigabit Router features dual-band wireless, allowing you to operate two concurrent, high-speed Wi-Fi bands for ultimate wireless performance. Surf the web or make important Internet phone calls on the 2.4 GHz band, while simultaneously streaming digital media on the 5 GHz band. What's more, each band can operate as a separate Wi-Fi network, giving you the ability to customize your network according to your connectivity needs. You can even configure a guest zone to give visitors Internet access without compromising the security of your SOHO network.



DIR-842 AC1200 MU-MIMO Wi-Fi Gigabit Router

Easy to Set Up, Easy to Secure

Sharing your Internet connection doesn't have to be a complicated process - just open a web browser to access the setup wizard and follow the easy step-by-step instructions to get started. Implement WPA/WPA2 wireless security in minutes with the wireless network setup wizard, or use Wi-Fi Protected Setup (WPS), which establishes a secure connection to new devices without the need to enter settings or create passwords. In addition, the built-in firewall requires no setup, protecting you against malicious attacks from the Internet, and access control features allow you to restrict access to your network giving you greater control over network users.



Technical Specifications		
General		
Device Interfaces	IEEE 802.11 ac/n/g/b/a wireless LAN 10/100/1000 Gigabit Ethernet WAN port	• Four 10/100/1000 Gigabit Ethernet LAN ports
LEDs	Power Internet WLAN	• LAN (x4) • WPS
Antenna Type	Four external antennas	
Operating Frequency	• 2.4 GHz band: 2400 - 2483.5 MHz	• 5 GHz band: 5150 - 5725 MHz
Standards	• IEEE 802.11ac • IEEE 802.11n • IEEE 802.11g • IEEE 802.3ab	• IEEE 802.11b • IEEE 802.11a • IEEE 802.3u
Minimum Requirements	 Windows 8/7/Vista or MAC OS X 10.6 or higher Internet Explorer 9, Firefox 20.0, Chrome 25.0, Safari 5.1, or other Java-enabled browser 	Network interface card Cable/DSL modem or other Internet Service Provider equipment with Ethernet port
Functionality		
Security	WPA & WPA2 (Wi-Fi Protected Access)	WPS (Wi-Fi Protected Setup)
Advanced Features	Web setup wizardQoS (Quality of Service)DMZ (Demilitarized Zone)	Firewall - Network Address Translation (NAT)Guest zoneIPv6 ready
Physical		
Dimensions	• 189.94 x 132.97 x 38.1 mm (7.47 x 5.23 x 1.5 inches)	
Weight	• 288 g	
Power Adaptor	• Input: 100 to 240 V AC, 50/60 Hz	Output: 12 V, 1 A
Temperature	• Operating: 0 to 40 °C (32 to 104 °F)	• Storage: -20 to 65 °C (-4 to 149 °F)
Humidity	Operating: 10% to 90% non-condensing	Storage: 5% to 95% non-condensing
Certifications	• CE • RoHS	FCC D-Link Green

DIR-842 AC1200 MU-MIMO Wi-Fi Gigabit Router

Order Information		
Part Number	Description	
DIR-842 / C1	AC1200 MU-MIMO Wi-Fi Gigabit Router	

¹Maximum wireless signal rate derived from IEEE Standard 802.11ac and IEEE 802.11n specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors will adversely affect wireless signal range. Wireless range and speed rates are D-Link relative performance measurements based on the wireless range and speed rates of a standard Wireless G product from D-Link. Maximum throughput based on D-Link 802.11n devices.

Updated 07/03/2015

